WEVER & DUCRÉ LIGHTING

FLYRA vertical 6.3

449684BM5

PROJECT


TYPE

NOTES


QUANTITY

DATE





Slim, vertically oriented tubular pendant luminaire made of ribbed glass; aluminium end caps in Black Matt + Champagne; 6 fixtures; No matching RAL; inclusive adjustable cable suspension max. 2500mm; phase-cut dim; light colour 2800 K; CRI ≥ 90; CRI (Colour Rendering Index) ≥ 90; 220 - 240 V; degree of protection IP20; Class 1; driver included; light source replaceable by Wever & Ducré or by a professional with explicit authorization; control gear replaceable by end-user;



LUMINAIRE

Ceiling
Suspended
Black Matt + Champagne
No matching RAL
IP20
Interior
2990 lm

LED MODULE

2800 K
CRI ≥ 90
L80 / 50000h
≤ 3 SDCM (initial MacAdam)

ELECTRICAL

phase-cut dim
220 - 240 V
system 35 W
Class I

PHYSICAL

diameter 40 mm
height 1555 mm
11.5 kg
cable length max. 10000 mm

['449684BM5'] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.

© Wever & Ducré BV · Spinnerijstraat 99/21 · 8500 Kortrijk · Belgium · www.weverducre.com