WEVER & DUCRÉ LIGHTING

# QITO 2.0

**198361GM3**

**PROJECT**


**TYPE**

**NOTES**


**QUANTITY**

**DATE**





Round ceiling recessed downlight made from die-cast aluminium; adjustable; with trim; surface Gunmetal Brushed; No matching RAL; inner ring black; installation without tools using blade springs; suitable for ceiling thickness of min. 5 mm; recessed depth 100mm; with COB (Chip on Board) technology for maximum efficiency; light colour 2700 K; ≤ 2 SDCM (initial MacAdam); CRI ≥ 90; beam angle 36°; 360° rotatable and 35° tiltable; degree of protection IP20; Class 3; driver not included; optional honeycomb louver available, to reduce glare; light source replaceable by Wever & Ducré or by a professional with explicit authorization;




**LUMINAIRE**

Ceiling
Recessed
tilt max 35 °
rotation 360 °
Gunmetal Brushed
No matching RAL
IP20
Interior
800 / 850 lm

**LED MODULE**

2700 K
CRI ≥ 90
L80 / 50000h
≤ 2 SDCM (initial MacAdam)
≤ 2 SDCM (initial MacAdam)

**OPTICAL**

Medium
beam angle 36°

**ELECTRICAL**

excl. driver
32 V / 34 V
Class III

**PHYSICAL**

diameter 103.5 mm
height 52.5 mm
0.2 kg
blade springs

**CUTOUT**

diameter 95-97 mm
min. ceiling thickness 5 mm
max. ceiling thickness 25 mm
recessed depth 100 mm

## ELECTRICAL ACCESSORIES

**DRIVER**

| TYPE | COLOUR | VOLTAGE | L·W·H (MM) | ITEM NUMBER |
|---|---|---|---|---|
| 10W \| 200mA \| 30-42V \| phase-cut dim \| 220-240VAC | | 30-42V | 85·22·41 | 90226402 |
| 10W \| 250mA \| 16-40V \| phase cut TE \| IP65 \| 110-240VAC | | 16-40V | 44·27·20 | 90226404 |
| 8W \| 200mA \| 10-40V \| DALI-2 push dim \| 220-240VAC | | 10-40V | 166·29·21 | 90246302 |

## OPTICAL ACCESSORIES

**HONEYCOMB LOUVRE**

| TYPE | COLOUR | VOLTAGE | Ø (MM) | ITEM NUMBER |
|---|---|---|---|---|
| QITO 2.0 | Black | | 41 | 915234B0 |

['198361GM3'] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.

© Wever & Ducré BV · Spinnerijstraat 99/21 · 8500 Kortrijk · Belgium · www.weverducre.com