WEVER & DUCRÉ LIGHTING

QITO 2.0

198361M5

PROJECT


TYPE

NOTES


QUANTITY

DATE





Round ceiling recessed downlight made from die-cast aluminium; adjustable; with trim; surface Champagne Brushed; No matching RAL; inner ring black; installation without tools using blade springs; suitable for ceiling thickness of min. 5 mm; recessed depth 100mm; with COB (Chip on Board) technology for maximum efficiency; light colour 3000 K; ≤ 2 SDCM (initial MacAdam); CRI ≥ 90; beam angle 36°; 360° rotatable and 35° tiltable; degree of protection IP20; Class 3; driver not included; optional honeycomb louver available, to reduce glare; light source replaceable by Wever & Ducré or by a professional with explicit authorization;



LUMINAIRE

Ceiling
Recessed
tilt max 35 °
rotation 360 °
Champagne Brushed
No matching RAL
IP20
Interior
840 / 890 lm

LED MODULE

3000 K
CRI ≥ 90
L80 / 50000h
≤ 2 SDCM (initial MacAdam)
≤ 2 SDCM (initial MacAdam)

OPTICAL

Medium
beam angle 36°

ELECTRICAL

excl. driver
32 V / 34 V
Class III

PHYSICAL

diameter 103.5 mm
height 52.5 mm
0.2 kg
blade springs

CUTOUT

diameter 95-97 mm
min. ceiling thickness 5 mm
max. ceiling thickness 25 mm
recessed depth 100 mm

ELECTRICAL ACCESSORIES

DRIVER

TYPE	COLOUR	VOLTAGE	L·W·H (MM)	ITEM NUMBER
10W | 200mA | 30-42V | phase-cut dim | 220-240VAC		30-42V	85·22·41	90226402
10W | 250mA | 16-40V | phase cut TE | IP65 | 110-240VAC		16-40V	44·27·20	90226404
8W | 200mA | 10-40V | DALI-2 push dim | 220-240VAC		10-40V	166·29·21	90246302

OPTICAL ACCESSORIES

HONEYCOMB LOUVRE

TYPE	COLOUR	VOLTAGE	Ø (MM)	ITEM NUMBER
QITO 2.0	Black		41	915234B0

['198361M5'] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.

© Wever & Ducré BV · Spinnerijstraat 99/21 · 8500 Kortrijk · Belgium · www.weverducre.com