WEVER & DUCRÉ LIGHTING

ORIS 0.8 Loxone

3274ALB5

PROJECT

TYPE

NOTES


QUANTITY

DATE





Rectangular wall recessed luminaire made from aluminium; surface Black Matt; powder coated; matt texture; RAL 9011; recessed depth 40mm; suitable for ceiling thickness of min. 12 mm; PCB; light colour 3000 K; CRI ≥ 90; degree of protection IP20; Class 3; Loxone ready; light source not replaceable;



LUMINAIRE

Wall
Recessed
Black Matt
RAL 9011 [a]
IP20
Interior
150 lm

LED MODULE

3000 K
CRI ≥ 90
L70 / 60000h

OPTICAL

Asymetric

ELECTRICAL

Loxone
24 V
Class III

PHYSICAL

length 80 mm
width 33 mm
height 80 mm
0.15 kg

CUTOUT

length 66 mm
width 66 mm
min. ceiling thickness 12 mm
recessed depth 40 mm

[a] Colour may deviate slightly due to production conditions

ORIS 0.8 Loxone

3274ALB5

MOUNTING ACCESSORIES

CONCRETE HOUSING FOR LOXONE

TYPE	COLOUR	VOLTAGE	L·W·H (MM)	ITEM NUMBER
ORIS 0.8 Loxone | RETO 0.8 Loxone			69·69·61	90012049

RECESSED HOUSING INCL. PLASTERKIT FOR LOXONE

TYPE	COLOUR	VOLTAGE	L·W·H (MM)	ITEM NUMBER
ORIS 0.8 Loxone | RETO 0.8 Loxone			160·68·160	90012053

['3274ALB5'] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.

© Wever & Ducré BV · Spinnerijstraat 99/21 · 8500 Kortrijk · Belgium · www.weverducre.com