WEVER & DUCRÉ LIGHTING

RAY SUSPENDED mini 3.0 Loxone

26017LLS3

PROJECT


TYPE

NOTES

QUANTITY

DATE

Cylindrical ceiling suspended luminaire made from die-cast aluminium; surface Live Simple; RAL 090 9005; with COB (Chip on Board) technology for maximum efficiency; 350mA; light colour 2700 K; CRI ≥ 90; beam angle 75°; 24 V; degree of protection IP20; Class 3; ceiling base included; Loxone ready; light source replaceable by Wever & Ducré or by a professional with explicit authorization;



LUMINAIRE

Ceiling
Suspended
Live Simple
RAL 090 9005 [a]
IP20
Interior
525 lm

LED MODULE

2700 K
CRI ≥ 90
L80 / 50000h

OPTICAL

Wide
beam angle 75°

ELECTRICAL

Loxone
24 V
Class III

PHYSICAL

diameter 43 mm
height 300 mm
0.33 kg
cable length 4000 mm
base included

[a] Colour may deviate slightly due to production conditions

['26017LLS3'] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.
© Wever & Ducré BV · Spinnerijstraat 99/21 · 8500 Kortrijk · Belgium · www.weverducre.com