WEVER & DUCRÉ LIGHTING

BLIEK ROUND petit trimless 1.0 Loxone

16456LW3

PROJECT


TYPE

NOTES


QUANTITY

DATE





Round ceiling recessed downlight made from die-cast aluminium; adjustable; surface White Matt; powder coated, matt texture; RAL 9010; inner ring black; with COB (Chip on Board) technology for maximum efficiency; light colour 2700 K; CRI ≥ 90; beam angle 31°; 355° rotatable and 60° tiltable; degree of protection IP20; Class 3; IC rated; Loxone ready; light source replaceable by Wever & Ducré or by a professional with explicit authorization;



LUMINAIRE

Ceiling
Semi-Recessed
tilt max 60 °
rotation 355 °
White Matt
RAL 9010 [a]
IP20
IC rated
Interior
495 lm

LED MODULE

2700 K
CRI ≥ 90
L70 / 55000h

OPTICAL

Medium (standard)
beam angle 31°

ELECTRICAL

Loxone
24 V
Class III

PHYSICAL

diameter 35 mm
height 55 mm
0.17 kg
alu plasterkit

CUTOUT

diameter 78-80 mm
recessed depth 80 mm
12,5, 15,25

[a] Colour may deviate slightly due to production conditions

BLIEK ROUND petit trimless 1.0 Loxone

16456LW3

OPTICAL ACCESSORIES

HONEYCOMB LOUVRE FOR LOXONE

TYPE	COLOUR	VOLTAGE	Ø (MM)	ITEM NUMBER
for CENO Loxone | LECA Loxone | PIRRO Loxone | BLIEK petit Loxone	Black		29	90051133

['16456LW3'] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.
© Wever & Ducré BV · Spinnerijstraat 99/21 · 8500 Kortrijk · Belgium · www.weverducre.com