WEVER & DUCRÉ LIGHTING

RONY ADJUST petit 1.0 Loxone

11046LW9

PROJECT


TYPE

NOTES


QUANTITY

DATE





Round ceiling recessed luminaire made from aluminium; surface White Matt; powder coated, matt texture; RAL 9010; installation without tools using wire springs; suitable for ceiling thickness of 4-22 mm; recessed depth 63mm; with COB (Chip on Board) technology for maximum efficiency; 350mA; light colour 2000 - 3000 K colour warm dimming; CRI ≥ 90; beam angle 39°; 355° rotatable and 35° tiltable; degree of protection IP20; Class 3; Loxone ready; light source replaceable by Wever & Ducré or by a professional with explicit authorization;



LUMINAIRE

Ceiling
Recessed
tilt max 35 °
rotation 355 °
White Matt
RAL 9010 [a]
IP20
IC rated
Interior
470 lm

LED MODULE

colour warm dimming
2000 - 3000 K
CRI ≥ 90
L70 / 50000h

OPTICAL

Medium (standard)
beam angle 39°

ELECTRICAL

Loxone
24 V
Class III

PHYSICAL

diameter 80 mm
height 58 mm
0.12 kg
wire springs

CUTOUT

diameter 70 mm
min. ceiling thickness 4 mm
max. ceiling thickness 22 mm
recessed depth 63 mm

[a] Colour may deviate slightly due to production conditions

['11046LW9'] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.

© Wever & Ducré BV · Spinnerijstraat 99/21 · 8500 Kortrijk · Belgium · www.weverducre.com