



PIRRO SPOT





CEILING SURFACE



77



279 | 309



2.0

LED 2x LED COB 5W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium powder coated

⊕ IP20 Δ 32° SDCM2 L70|55K 0.30kg

4.0


LED 4x LED COB 5W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium powder coated

⊕ IP20 Δ 32° SDCM2 L70|55K 0.48kg

6.0

LED 6x LED COB 5W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium powder coated

⊕ IP20 Δ 32° SDCM2 L70|55K 0.80kg



OPTIONAL

honeycomb louver

CODE 90051131

| CODE | |
|------|----------|
| | 151264E_ |
| | 151264J_ |
| | 151264K_ |
| | 151264B_ |

| LIGHT COLOUR | LUMEN CRI | CODE |
|--------------|-----------|------|
| 2700K | 2x360 >90 | 3 |
| 3000K | 2x380 >90 | 5 |

| CODE | |
|------|----------|
| | 151464E_ |
| | 151464J_ |
| | 151464K_ |
| | 151464B_ |

| LIGHT COLOUR | LUMEN CRI | CODE |
|--------------|-----------|------|
| 2700K | 4x360 >90 | 3 |
| 3000K | 4x380 >90 | 5 |

| CODE | |
|------|----------|
| | 151664E_ |
| | 151664J_ |
| | 151664K_ |
| | 151664B_ |

| LIGHT COLOUR | LUMEN CRI | CODE |
|--------------|-----------|------|
| 2700K | 6x360 >90 | 3 |
| 3000K | 6x380 >90 | 5 |