



PROJECT

TYPE

NOTES

QUANTITY

DATE



Floor surface mounted luminaire made from die-cast aluminium; surface Bronze; powder coated; matt texture; RAL 075 30 10; opal PC cover; PCB; light colour 2700 K; ≤ 3 SDCM (initial MacAdam); CRI ≥ 90 ; 24 V; degree of protection IP65; Class 3; Plug & Play connector system; driver not included; inclusive 2500mm cable; ground spike included; light source replaceable by Wever & Ducré or by a professional with explicit authorization;

LUMINAIRE

Floor
Surface
Bronze
RAL 075 30 10 ^a
IP65
Exterior
395 lm

LED MODULE

2700 K
CRI ≥ 90
L80 / 50000h
 ≤ 3 SDCM (initial MacAdam)

OPTICAL

Opal
CIE flux code: 20 45 72 49 100



ELECTRICAL

24 V
Class III

PHYSICAL

diameter 20 mm
height 900 mm
0.45 kg

LIGHT DISTRIBUTION



^a Colour may deviate slightly due to production conditions


Maintenance Factor

Operating Time [h]	10.000	20.000	30.000	40.000	50.000
LLMF	0.98	0.97	0.95	0.93	0.92
LSF	1	1	1	1	1

MF	LMF × RSMF × LLMF × LSF	RSMF ^a	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF ^a	Luminaire Maintenance Factor	LSF	Lamp Survival Factor

^aAccording to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

ELECTRICAL ACCESSORIES
PLUG & PLAY DRIVER

TYPE	COLOUR	VOLTAGE	L·W·H (MM)	ITEM NUMBER
30W IP67 220-240VAC		24V	118-35-26	90018014
75W IP67 220-240VAC		24V	162,5-43-32	90018015
plug type L 50W 24V IP67 100-277VAC		24V	110-63-32	C90018024
plug type L 100W 24V IP67 100-277VAC		24V	153-63-32	C90018025
plug type B 50W 24V IP67 100-277VAC		24V	110-63-32	L90018024
plug type B 100W 24V IP67 100-277VAC		24V	153-63-32	L90018025

PLUG & PLAY DRIVER CH

TYPE	COLOUR	VOLTAGE	L·W·H (MM)	ITEM NUMBER
30W IP67		24V	150-48-31	90018016
60W IP67		24V	167-48-32	90018017

PLUG & PLAY DRIVER UK

TYPE	COLOUR	VOLTAGE	L·W·H (MM)	ITEM NUMBER
30W IP67		24V	150-48-31	90018018
60W IP67		24V	167-48-32	90018019

PLUG & PLAY EXTENSION CABLE

TYPE	COLOUR	VOLTAGE	LENGTH (MM)	ITEM NUMBER
2.5 m IP67			2500	90014502
5 m IP67			5000	90014503
0.5 m IP67			500	90014505
1 m IP67			1000	90014506

PLUG & PLAY STRAIGHT CONNECTOR

TYPE	COLOUR	VOLTAGE	LENGTH (MM)	ITEM NUMBER
			200	90014504

PLUG & PLAY T-CONNECTOR

TYPE	COLOUR	VOLTAGE	L·W·H (MM)	ITEM NUMBER
			48-24-15	90014501