




PROJECT _____

TYPE _____


NOTES _____

QUANTITY _____

DATE _____



Floor surface mounted luminaire made from die-cast aluminium; surface Bronze; powder coated; matt texture; RAL 075 30 10; opal PC cover; PCB 3-step binning; light colour 2700 K; ≤ 3 SDCM (initial MacAdam); CRI ≥ 90 ; 24 V; degree of protection IP65; Class 3; Plug & Play connector system; driver not included; inclusive 2500mm cable; ground spike included; light source replaceable by Wever & Ducré or by a professional with explicit authorization;



LUMINAIRE

Floor _____

Surface _____

Bronze _____

RAL 075 30 10 ^a _____

IP65 _____

Exterior _____

330 lm _____

LED Module

2700 K _____

CRI ≥ 90 _____

L80 / 50000h _____

≤ 3 SDCM (initial MacAdam) _____

Optical

Opal _____

CIE flux code: 20 45 72 49 100 _____

Electrical

24 V _____

Class III _____

Standard _____

Physical

diameter 20 mm _____

height 600 mm _____


0.36 kg _____

datasheet.quicksum.material

Aluminium _____

^a Colour may deviate slightly due to production conditions

LIGHT DISTRIBUTION




Maintenance Factor

Operating Time [h]	10.000	20.000	30.000	40.000	50.000
LLMF	0.98	0.97	0.95	0.93	0.92
LSF	1	1	1	1	1

$$MF = LMF \times RSMF \times LLMF \times LSF$$

MF Maintenance Factor

RSMF^a Room Surface Maintenance Factor

LLMF Lamp Lumens Maintenance Factor

LMF^a Luminaire Maintenance Factor

LSF Lamp Survival Factor

^aAccording to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

ELECTRICAL ACCESSORIES
Plug & Play Driver

Type	Colour	Voltage	L·W·H (MM)	Item number
30W IP67			118-35-26	90018014
75W IP67			162,5-43-32	90018015

Plug & Play Driver CH

Type	Colour	Voltage	L·W·H (MM)	Item number
30W IP67			150-48-31	90018016
75W IP67			167-48-32	90018017

Plug & Play Driver UK

Type	Colour	Voltage	L·W·H (MM)	Item number
30W IP67			150-48-31	90018018
75W IP67			167-48-32	90018019

Plug & Play Extension Cable

Type	Colour	Voltage	Length (MM)	Item number
2,5 m IP67			2500	90014502
5 m IP67			5000	90014503
0.5 m IP67			500	90014505
1 m IP67			1000	90014506

Plug & Play Straight Connector

Type	Colour	Voltage	Length (MM)	Item number
			200	90014504

Plug & Play T-Connector

Type	Colour	Voltage	L·W·H (MM)	Item number
			48-24-15	90014501