



PROJECT

TYPE


NOTES

QUANTITY

DATE



Cylindrical outdoor floor projector; surface Bronze; powder coated; matt texture; RAL 075 30 10; PCB 3-step binning; light colour 2700 K; CRI ≥ 90; 24 V; 135° tiltable; degree of protection IP65; Class 3; driver not included; ground spike included; light source replaceable by Wever & Ducré or by a professional with explicit authorization;



LUMINAIRE

Floor
 Surface
 tilt max 135 °
 Bronze
 RAL 075 30 10 ^a
 IP65
 Exterior
 245 lm

LED Module

2700 K
 CRI ≥ 90
 L80 / 50000h
 ≤ 3 SDCM (initial MacAdam)

Optical

Medium (standard)
 beam angle 30°
 CIE flux code: 98 100 100 100

Electrical

24 V
 Class III
 Standard

Physical


diameter 34 mm
 height 76 mm
 0.29 kg

datasheet.quicksum.material

Aluminium

^a Colour may deviate slightly due to production conditions

LIGHT DISTRIBUTION




CONE DIAGRAM

medium (standard) 31°

h (m)	EO° (lx)	ø (m)
1	693	0.56
2	173	1.11
3	77	1.67
4	43	2.22
5	28	2.78

ELECTRICAL ACCESSORIES
Plug & Play Driver

Type	Colour	Voltage	L·W·H (MM)	Item number
30W IP67		24V	118-35-26	90018014
75W IP67		24V	162,5-43-32	90018015

Plug & Play Driver CH

Type	Colour	Voltage	L·W·H (MM)	Item number
30W IP67		24V	150-48-31	90018016
75W IP67		24V	167-48-32	90018017

Plug & Play Driver UK

Type	Colour	Voltage	L·W·H (MM)	Item number
30W IP67		24V	150-48-31	90018018
75W IP67		24V	167-48-32	90018019

Plug & Play Extension Cable

Type	Colour	Voltage	Length (MM)	Item number
2,5 m IP67			2500	90014502
5 m IP67			5000	90014503
0.5 m IP67			500	90014505
1 m IP67			1000	90014506

Plug & Play Straight Connector

Type	Colour	Voltage	Length (MM)	Item number
			200	90014504

Plug & Play T-Connector

Type	Colour	Voltage	L·W·H (MM)	Item number
			48-24-15	90014501