



PROJECT

TYPE


NOTES

QUANTITY

DATE



Cylindrical outdoor floor projector; surface Anthracite Grey; powder coated; matt texture; RAL 7016; PCB 3-step binning; light colour 2700 K; CRI ≥ 90 ; 24 V; 135° tiltable; degree of protection IP65; Class 3; driver not included; ground spike included; light source replaceable by Wever & Ducré or by a professional with explicit authorization;



LUMINAIRE

Floor
Surface
tilt max 135 °
Anthracite Grey
RAL 7016 ^a
IP65
Exterior
245 lm

LED Module

2700 K
CRI ≥ 90
L80 / 50000h
 ≤ 3 SDCM (initial MacAdam)
243 lm
66 lm/W ^b

Optical

Medium (standard)
beam angle 30°
CIE flux code: 98 100 100 100 100


Electrical

24 V
Class III

Physical

diameter 34 mm
height 76 mm
0.29 kg

LIGHT DISTRIBUTION



^a Colour may deviate slightly due to production conditions

^b Without electrical and optical losses


CONE DIAGRAM

medium (standard) 31°

h (m)	E0° (lx)	ø (m)
1	693	0.56
2	173	1.11
3	77	1.67
4	43	2.22
5	28	2.78

ELECTRICAL ACCESSORIES
Plug & Play Driver

Type	Colour	Voltage	L·W·H (MM)	Item number
30W IP67		24V	118-35-26	90018014
75W IP67		24V	162,5-43-32	90018015

Plug & Play Driver CH

Type	Colour	Voltage	L·W·H (MM)	Item number
30W IP67		24V	150-48-31	90018016
75W IP67		24V	167-48-32	90018017

Plug & Play Driver UK

Type	Colour	Voltage	L·W·H (MM)	Item number
30W IP67		24V	150-48-31	90018018
75W IP67		24V	167-48-32	90018019

Plug & Play Extension Cable

Type	Colour	Voltage	Length (MM)	Item number
2,5 m IP67			2500	90014502
5 m IP67			5000	90014503
0.5 m IP67			500	90014505
1 m IP67			1000	90014506

Plug & Play Straight Connector

Type	Colour	Voltage	Length (MM)	Item number
			200	90014504

Plug & Play T-Connector

Type	Colour	Voltage	L·W·H (MM)	Item number
			48-24-15	90014501