



PROJECT

TYPE

NOTES

QUANTITY


DATE



IP65



Floor surface mounted luminaire made from die-cast aluminium; surface Bronze; powder coated; matt texture; RAL 075 30 10; PCB 3-step binning; phase-cut dim; light colour 3000 K; CRI ≥ 80; 220 - 240 V; degree of protection IP65; Class I; fixation base not included; driver included; light source replaceable by Wever & Ducré or by a professional with explicit authorization; control gear replaceable by end-user;



LUMINAIRE

Floor
Surface
Bronze
RAL 075 30 10 ^a
IP65
Exterior
610 lm

LED Module

3000 K
CRI ≥ 80
L80 / 50000h
≤ 3 SDCM (initial MacAdam)

Optical

Asymetric
CIE flux code: 68 95 100 100 100


Electrical

phase-cut dim
220 - 240 V
system 11.4 W
Class I

Physical

diameter 80 mm
height 28 mm
0.38 kg

LIGHT DISTRIBUTION



^a Colour may deviate slightly due to production conditions



BASE

Pole 250

Type	Colour	Voltage	Ø-H (MM)	Item number
GATE ROUND 2.0	Anthracite Grey		80-250	910124A0
GATE ROUND 2.0	Bronze		80-250	910124Q0

Pole 450

Type	Colour	Voltage	Ø-H (MM)	Item number
GATE ROUND 2.0	Anthracite Grey		80-450	910125A0
GATE ROUND 2.0	Bronze		80-450	910125Q0

Pole 650

Type	Colour	Voltage	Ø-H (MM)	Item number
GATE ROUND 2.0	Anthracite Grey		80-650	910126A0
GATE ROUND 2.0	Bronze		80-650	910126Q0