WEVER & DUCRÉ LIGHTING

GATE ROUND 2.0

7582A4Q2

PROJECT

TYPE

NOTES


QUANTITY

DATE



IP65

Floor surface mounted luminaire made from die-cast aluminium; surface Bronze; powder coated; matt texture; RAL 075 30 10; PCB; phase-cut dim; light colour 2700 K; CRI ≥ 80; 220 - 240 V; degree of protection IP65; Class 1; fixation base not included; driver included; light source replaceable by Wever & Ducré or by a professional with explicit authorization; control gear replaceable by end-user;



LUMINAIRE

Floor
Surface
Bronze
RAL 075 30 10 [a]
IP65
Exterior
580 lm

LED MODULE

2700 K
CRI ≥ 80
L80 / 50000h
≤ 3 SDCM (initial MacAdam)

OPTICAL

Asymetric
CIE flux code: 68 95 100 100 100

ELECTRICAL


phase-cut dim
220 - 240 V
system 11.4 W
Class I

PHYSICAL

diameter 80 mm
height 28 mm
0.38 kg

[a] Colour may deviate slightly due to production conditions

LIGHT DISTRIBUTION



GATE ROUND 2.0

7582A4Q2

BASE

POLE 250

TYPE	COLOUR	VOLTAGE	Ø·H (MM)	ITEM NUMBER
GATE ROUND 2.0	Anthracite Grey		80·250	910124A0
GATE ROUND 2.0	Bronze		80·250	910124Q0

POLE 450

TYPE	COLOUR	VOLTAGE	Ø·H (MM)	ITEM NUMBER
GATE ROUND 2.0	Anthracite Grey		80·450	910125A0
GATE ROUND 2.0	Bronze		80·450	910125Q0

POLE 650

TYPE	COLOUR	VOLTAGE	Ø·H (MM)	ITEM NUMBER
GATE ROUND 2.0	Anthracite Grey		80·650	910126A0
GATE ROUND 2.0	Bronze		80·650	910126Q0

['7582A4Q2'] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.

© Wever & Ducré BV · Spinnerijstraat 99/21 · 8500 Kortrijk · Belgium · www.weverducre.com