



PROJECT

TYPE


NOTES

QUANTITY

DATE



Floor surface mounted luminaire made from die-cast aluminium; surface Anthracite Grey; powder coated; matt texture; RAL 7016; PCB 3-step binning; phase-cut dim; light colour 2700 K; CRI ≥ 80; 220 - 240 V; degree of protection IP65; Class 1; fixation base not included; driver included; light source replaceable by Wever & Ducré or by a professional with explicit authorization; control gear replaceable by end-user;



LUMINAIRE

Floor _____
 Surface _____
 Anthracite Grey _____
 RAL 7016 ^a _____
 IP65 _____
 Exterior _____
 580 lm _____

LED Module

2700 K _____
 CRI ≥ 80 _____
 L80 / 50000h _____
 ≤ 3 SDCM (initial MacAdam) _____

Optical

Asymetric _____
 CIE flux code: 68 95 100 100 _____
 100 _____

Electrical


phase-cut dim _____
 220 - 240 V _____
 system 11.4 W _____
 Class I _____

Physical

diameter 80 mm _____
 height 28 mm _____
 0.38 kg _____

^a Colour may deviate slightly due to production conditions

LIGHT DISTRIBUTION



[7582A4A2] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.



BASE

Pole 250

Type	Colour	Voltage	Ø-H (MM)	Item number
GATE 2.0	Anthracite Grey		80-250	910124A0
GATE 2.0	Bronze		80-250	910124Q0

Pole 450

Type	Colour	Voltage	Ø-H (MM)	Item number
GATE 2.0	Anthracite Grey		80-450	910125A0
GATE 2.0	Bronze		80-450	910125Q0

Pole 650

Type	Colour	Voltage	Ø-H (MM)	Item number
GATE 2.0	Anthracite Grey		80-650	910126A0
GATE 2.0	Bronze		80-650	910126Q0