



**PROJECT** \_\_\_\_\_

**TYPE** \_\_\_\_\_


**NOTES** \_\_\_\_\_

**QUANTITY** \_\_\_\_\_

**DATE** \_\_\_\_\_



Floor surface mounted luminaire made from die-cast aluminium; surface Bronze; powder coated; matt texture; RAL 075 30 10; PCB 3-step binning; phase-cut dim; light colour 2700 K; ≤ 3 SDCM (initial MacAdam); CRI ≥ 80; 220 - 240 V; degree of protection IP65; Class 1; fixation base not included; driver included; light source replaceable by Wever & Ducré or by a professional with explicit authorization; control gear replaceable by end-user;



**LUMINAIRE**

Floor
Surface
Bronze
RAL 075 30 10 <sup>a</sup>
IP65
Exterior
400 lm

**LED Module**

2700 K
CRI ≥ 80
L80 / 50000h
≤ 3 SDCM (initial MacAdam)

**Optical**

Asymetric
CIE flux code: 69 95 100 100
100

**Electrical**

phase-cut dim
220 - 240 V
system 8.2 W
Class I
Standard

**Physical**


diameter 80 mm
height 28 mm
0.38 kg

**datasheet.quicksum.material**

Aluminium
-----------

<sup>a</sup> Colour may deviate slightly due to production conditions

**LIGHT DISTRIBUTION**



[7581A4Q2] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.


**Maintenance Factor**

Operating Time [h]	10.000	20.000	30.000	40.000	50.000
LLMF	0.98	0.96	0.93	0.91	0.88
LSF	1	1	1	1	1

$$MF = LMF \times RSMF \times LLMF \times LSF$$

MF Maintenance Factor

LMF<sup>a</sup> Luminaire Maintenance Factor

RSMF<sup>a</sup> Room Surface Maintenance Factor

LLMF Lamp Lumens Maintenance Factor

LSF Lamp Survival Factor

<sup>a</sup>According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

**BASE**
**Pole 250**

Type	Colour	Voltage	Ø·H (MM)	Item number
GATE ROUND 1.0	Anthracite Grey		80-250	910121A0
GATE ROUND 1.0	Bronze		80-250	910121Q0

**Pole 450**

Type	Colour	Voltage	Ø·H (MM)	Item number
GATE ROUND 1.0	Anthracite Grey		80-450	910122A0
GATE ROUND 1.0	Bronze		80-450	910122Q0

**Pole 650**

Type	Colour	Voltage	Ø·H (MM)	Item number
GATE ROUND 1.0	Anthracite Grey		80-650	910123A0
GATE ROUND 1.0	Bronze		80-650	910123Q0