



**PROJECT** \_\_\_\_\_

**TYPE** \_\_\_\_\_


**NOTES** \_\_\_\_\_

**QUANTITY** \_\_\_\_\_

**DATE** \_\_\_\_\_



Round floor recessed luminaire made from aluminium and glass; with trim; surface Black Matt; RAL 9011; recessed depth 63 mm; with COB (Chip on Board) technology for maximum efficiency; light colour 3000 K;  $\leq 2$  SDCM (initial MacAdam); CRI  $\geq 90$ ; beam angle 30°; degree of protection IP65; Class 3; driver not included; optional recessed ground housing available; light source not replaceable;



**LUMINAIRE**

- \_\_\_\_\_ Floor
- \_\_\_\_\_ Recessed
- \_\_\_\_\_ Black Matt
- \_\_\_\_\_ RAL 9011 <sup>a</sup>
- \_\_\_\_\_ IP65
- \_\_\_\_\_ IK08
- \_\_\_\_\_ Exterior
- \_\_\_\_\_ 410 lm

**LED Module**

- \_\_\_\_\_ 3000 K
- \_\_\_\_\_ CRI  $\geq 90$
- \_\_\_\_\_ L80 / 50000h
- \_\_\_\_\_  $\leq 2$  SDCM (initial MacAdam)

**Optical**

- \_\_\_\_\_ Medium (standard)
- \_\_\_\_\_ beam angle 30°
- \_\_\_\_\_ CIE flux code: 96 99 100 100 100

**Electrical**

- \_\_\_\_\_ excl. driver
- \_\_\_\_\_ 9 V
- \_\_\_\_\_ Class III
- \_\_\_\_\_ Standard

**Physical**


- \_\_\_\_\_ diameter 62 mm
- \_\_\_\_\_ height 57 mm
- \_\_\_\_\_ 0.34 kg

**Cutout**

- \_\_\_\_\_ diameter 47-49 mm
- \_\_\_\_\_ recessed depth 63 mm

<sup>a</sup> Colour may deviate slightly due to production conditions

**LIGHT DISTRIBUTION**





## CONE DIAGRAM

medium (standard) 32°

h (m)	E0° (lx)	ø (m)
1	1080	0.56
2	270	1.13
3	120	1.69
4	70	2.26
5	40	2.82

## ELECTRICAL ACCESSORIES

### Driver

Type	Colour	Voltage	L·W·H (MM)	Item number
7W   500mA   5-14.5V   IP67		5-14.5V	57·41·24	90214301
6.5W   500mA   7-13V   phase-cut dim		7-13V	122·41·23	90224301

## MOUNTING ACCESSORIES

### Ground Housing

Type	Colour	Voltage	Ø·H (MM)	Item number
MAP 0.6   CHART 0.6   BLINK TRIM   TRIMLESS			132·105	90012201