



PROJECT

TYPE

NOTES

QUANTITY


DATE



IP65



Floor surface mounted luminaire made from die-cast aluminium; surface Bronze; powder coated; matt texture; RAL 075 30 10; down light emission; PCB; phase-cut dim; light colour 3000 K; ≤ 3 SDCM (initial MacAdam); CRI ≥ 90 ; 220 - 240 V; degree of protection IP65; Class 1; driver included; fixation base not included; optional ground fixation available; light source not replaceable; control gear not replaceable;



LUMINAIRE

Floor
Surface
Bronze
RAL 075 30 10 ^a
IP65
Exterior
1130 lm

LED Module

3000 K
CRI ≥ 90
L80 / 50000h
 ≤ 3 SDCM (initial MacAdam)

Optical

CIE flux code: 50 81 97 100 100


Electrical

phase-cut dim
220 - 240 V
system 18.3 W
Class I

Physical

length 133 mm
width 148 mm
height 52 mm
0.82 kg

LIGHT DISTRIBUTION



^a Colour may deviate slightly due to production conditions



Maintenance Factor

Operating Time [h]	10.000	20.000	30.000	40.000	50.000
LLMF	0.98	0.96	0.94	0.93	0.91
LSF	1	1	1	1	1

MF	LMF × RSMF × LLMF × LSF	RSMF ^a	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF ^a	Luminaire Maintenance Factor	LSF	Lamp Survival Factor

^aAccording to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

BASE

Ground Fixation Plate

Type	Colour	Voltage	Ø·H (MM)	Item number
KIOSK SWAM			80·10	90019019

Pole 400 straight

Type	Colour	Voltage	Length (MM)	Item number
KIOSK	Anthracite Grey		400	910101A0
KIOSK	Bronze		400	910101Q0

Pole 600 straight

Type	Colour	Voltage	Length (MM)	Item number
KIOSK	Anthracite Grey		600	910102A0
KIOSK	Bronze		600	910102Q0

Pole 800 straight

Type	Colour	Voltage	Length (MM)	Item number
KIOSK	Anthracite Grey		800	910103A0
KIOSK	Bronze		800	910103Q0