




## PROJECT

## TYPE

## NOTES

## QUANTITY

## DATE



Free standing luminaire made from aluminium; surface White Matt; powder coated; matt texture; RAL 9010; with COB (Chip on Board) technology for maximum efficiency; light colour 2700 K; CRI  $\geq 90$ ; beam angle 30°; spotlight head 360° rotatable and 145° tiltable; degree of protection IP20; Class 2; cable plug with dimmer switch; driver included; light source replaceable by Wever & Ducré or by a professional with explicit authorization;



## LUMINAIRE

Floor  
Surface  
tilt max 145 °  
rotation 360 °  
White Matt  
RAL 9010 <sup>a</sup>  
IP20  
Interior  
505 lm

## LED Module

2700 K  
CRI  $\geq 90$   
L80 / 50000h  
 $\leq 3$  SDCM (initial MacAdam)

## Optical

Medium (standard)  
beam angle 30°  
UGR  $\leq 19$   
CIE flux code: 97 100 100 100 100


## Electrical

dimming on cable  
220 - 240 V  
system 7.6 W  
Class II

## Physical

diameter 27 mm  
height 127 mm  
2.83 kg  
cable plug with dimmer switch

## LIGHT DISTRIBUTION



<sup>a</sup> Colour may deviate slightly due to production conditions