



PROJECT _____

TYPE _____

NOTES _____

QUANTITY _____

DATE _____



Free standing luminaire made from aluminium; surface Black Matt; powder coated; matt texture; RAL 9011; with COB (Chip on Board) technology for maximum efficiency; light colour 2700 K; CRI ≥ 90; beam angle 30°; spotlight head 360° rotatable and 145° tiltable; degree of protection IP20; Class 2; cable plug with dimmer switch; driver included; light source replaceable by Wever & Ducré or by a professional with explicit authorization;

LUMINAIRE

Floor _____

Surface _____

tilt max 145 ° _____

rotation 360 ° _____

Black Matt _____

RAL 9011 ^a _____

IP20 _____

Interior _____

505 lm _____

LED Module

2700 K _____

CRI ≥ 90 _____

L80 / 50000h _____

≤ 3 SDCM (initial MacAdam) _____

Optical

Medium (standard) _____

beam angle 30° _____

UGR ≤ 19 _____

CIE flux code: 97 100 100 100 100 _____

Electrical

dimming on cable _____

220 - 240 V _____

system 7.6 W _____

Class II _____

Standard _____

Physical

diameter 27 mm _____

height 127 mm _____

2.83 kg _____

cable plug with dimmer switch _____

datasheet.quicksum.material

Aluminium _____

^a Colour may deviate slightly due to production conditions

LIGHT DISTRIBUTION

