WEVER & DUCRÉ LIGHTING

RETO 0.8

3451A1M5

PROJECT

TYPE

NOTES

QUANTITY

DATE





Square wall recessed luminaire made from aluminium; surface Champagne Brushed; powder coated; matt texture; No matching RAL; recessed depth 40mm; suitable for ceiling thickness of min. 12 mm; PCB; light colour 3000 K; ≤ 3 SDCM (initial MacAdam); CRI ≥ 90; degree of protection IP20; Class 3; driver not included; light source not replaceable;



LUMINAIRE

Wall
Recessed
Champagne Brushed
No matching RAL
IP20
Interior
110 lm

LED MODULE

3000 K
CRI ≥ 90
L80 / 50000h
≤ 3 SDCM (initial MacAdam)

OPTICAL

Asymetric
CIE flux code: 51 75 91 88 100

ELECTRICAL

excl. driver
9 V
Class III

PHYSICAL

length 80 mm
width 16 mm
height 80 mm
0.23 kg

CUTOUT

length 66 mm
width 66 mm
min. ceiling thickness 12 mm
recessed depth 40 mm

LIGHT DISTRIBUTION



MOUNTING ACCESSORIES

CONCRETE HOUSING

TYPE	COLOUR	VOLTAGE	L·W·H (MM)	ITEM NUMBER
ORIS 0.8 | RETO 0.8			69·69·61	90012046

RECESSED HOUSING INCL. PLASTERKIT

TYPE	COLOUR	VOLTAGE	L·W·H (MM)	ITEM NUMBER
ORIS 0.8 | RETO 0.8			109·109·74	90012047

ELECTRICAL ACCESSORIES

DRIVER

TYPE	COLOUR	VOLTAGE	L·W·H (MM)	ITEM NUMBER
6W | 350mA | 3-22V | 100-240VAC		3-22V	68·35·21	90213202

['3451A1M5'] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.

© Wever & Ducré BV · Spinnerijstraat 99/21 · 8500 Kortrijk · Belgium · www.weverducre.com