



PROJECT _____

TYPE _____


NOTES _____

QUANTITY _____

DATE _____



Square wall recessed luminaire made from aluminium; surface Champagne Brushed; powder coated; matt texture; No matching RAL; recessed depth 40 mm; suitable for ceiling thickness of min. 12 mm; PCB 3-step binning; light colour 3000 K; ≤ 3 SDCM (initial MacAdam); CRI ≥ 90 ; degree of protection IP20; Class 3; driver not included; light source not replaceable;



LUMINAIRE

Wall _____
 Recessed _____
 Champagne Brushed _____
 No matching RAL _____
 IP20 _____
 Interior _____
 110 lm _____

LED Module

3000 K _____
 CRI ≥ 90 _____
 L80 / 50000h _____
 ≤ 3 SDCM (initial MacAdam) _____

Optical

Asymetric _____
 CIE flux code: 51 75 91 88 100 _____

Electrical

excl. driver _____
 9 V _____
 Class III _____
 Standard _____

Physical

length 80 mm _____
 width 16 mm _____
 height 80 mm _____
 0.23 kg _____


Cutout

length 66 mm _____
 width 66 mm _____
 min. ceiling thickness 12 mm _____
 recessed depth 40 mm _____

datasheet.quicksum.material

Aluminium _____

LIGHT DISTRIBUTION



[‘3451A1M5’] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.

3451A1M5



MOUNTING ACCESSORIES

Concrete Housing

Type	Colour	Voltage	L·W·H (MM)	Item number
RETO 0.8			69-69-61	90012046

Recessed Housing incl. plasterkit

Type	Colour	Voltage	L·W·H (MM)	Item number
RETO 0.8			109-109-74	90012047

ELECTRICAL ACCESSORIES

Driver

Type	Colour	Voltage	L·W·H (MM)	Item number
6W 350mA 3-22V		3-22V	68-35-21	90213202