



PROJECT

TYPE


NOTES

QUANTITY

DATE



Square wall recessed luminaire made from aluminium; surface Aluminium Brushed; powder coated; matt texture; recessed depth 40 mm; suitable for ceiling thickness of min. 12 mm; PCB 3-step binning; light colour 3000 K; ≤ 3 SDCM (initial MacAdam); CRI ≥ 90 ; degree of protection IP20; Class 3; driver not included; light source not replaceable;



LUMINAIRE

Wall
Recessed
Aluminium Brushed
IP20
Interior
110 lm

LED Module

3000 K
CRI ≥ 90
L80 / 50000h
 ≤ 3 SDCM (initial MacAdam)

Optical

Asymetric
CIE flux code: 51 75 91 88 100

Electrical

excl. driver
9 V
Class III


Physical

length 80 mm
width 16 mm
height 80 mm
0.23 kg

Cutout

length 66 mm
width 66 mm
min. ceiling thickness 12 mm
recessed depth 40 mm

LIGHT DISTRIBUTION



3451A1L5


MOUNTING ACCESSORIES

Concrete Housing

Type	Colour	Voltage	L·W·H (MM)	Item number
ORIS 0.8 RETO 0.8			69-69-61	90012046

Recessed Housing incl. plasterkit

Type	Colour	Voltage	L·W·H (MM)	Item number
ORIS 0.8 RETO 0.8			109-109-74	90012047

ELECTRICAL ACCESSORIES

Driver

Type	Colour	Voltage	L·W·H (MM)	Item number
6W 350mA 3-22V		3-22V	68-35-21	90213202