




PROJECT

TYPE

NOTES

QUANTITY

DATE



Ring shaped suspended luminaire made from die-cast aluminium; inclusive adjustable cable suspension max. 4000mm and base in Champagne; surface Champagne; wet painted, smooth semi glossy; No matching RAL; silicone cover; PCB; phase-cut dim; light colour 2700 K; ≤ 3 SDCM (initial MacAdam); CRI ≥ 90 ; 220 - 240 V; degree of protection IP20; Class 2; driver included; light source replaceable by Wever & Ducré or by a professional with explicit authorization; control gear replaceable by end-user;

LUMINAIRE

Ceiling
Suspended
Champagne
No matching RAL
IP20
Interior

LED MODULE

2700 K
CRI ≥ 90
L80 / 100000h
 ≤ 3 SDCM (initial MacAdam)

OPTICAL


Opal

ELECTRICAL

phase-cut dim
220 - 240 V
Class II

PHYSICAL

diameter 380 mm
height 25 mm
0.59 kg




Maintenance Factor

Operating Time [h]	10.000	20.000	30.000	40.000	50.000
LLMF	0.98	0.96	0.94	0.93	0.91
LSF	1	1	1	1	1

MF	$LMF \times RSMF \times LLMF \times LSF$	RSMF ^a	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF ^a	Luminaire Maintenance Factor	LSF	Lamp Survival Factor

^aAccording to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.