



PROJECT _____

TYPE _____

NOTES _____

QUANTITY _____

DATE _____



LUMINAIRE

Ceiling _____
 Surface _____
 Bronze Brushed _____
 RAL 7013 ^a _____
 IP20 _____
 Interior _____
 440 lm _____

LED Module

3000 K _____
 CRI ≥ 90 _____
 L80 / 55000h _____
 ≤ 2 SDCM (initial MacAdam) _____
 555 lm _____
 107 lm/W ^b _____

Optical

Medium (standard) _____
 beam angle 30° _____
 CIE flux code: 93 97 99 100 _____
 100 _____

Electrical

phase-cut dim _____
 220 - 240 V _____
 system 6.8 W _____
 Class I _____
 Standard _____

Physical



length 70 mm _____
 width 70 mm _____
 height 85 mm _____
 0.25 kg _____

datasheet.quicksum.material


Aluminium _____

^a Colour may deviate slightly due to production conditions
^b Without electrical and optical losses

LIGHT DISTRIBUTION



Squared ceiling surface mounted downlight made from die-cast aluminium; surface Bronze Brushed; RAL 7013; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 3000 K; ≤ 2 SDCM (initial MacAdam); CRI ≥ 90; beam angle 30°; degree of protection IP20; Class 1; driver included; light source replaceable by Wever & Ducré or by a professional with explicit authorization; control gear replaceable by end-user;



[‘258154QQ5’] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.



Maintenance Factor

Operating Time [h]	10.000	20.000	30.000	40.000	50.000
LLMF	0.98	0.95	0.93	0.9	0.88
LSF	1	1	1	1	1

MF	$LMF \times RSMF \times LLMF \times LSF$	RSMF ^a	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF ^a	Luminaire Maintenance Factor	LSF	Lamp Survival Factor

^aAccording to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.