



**PROJECT** \_\_\_\_\_

---

**TYPE** \_\_\_\_\_

---

**NOTES** \_\_\_\_\_


---

**QUANTITY** \_\_\_\_\_


---

**DATE** \_\_\_\_\_

---



Squared ceiling surface mounted downlight made from die-cast aluminium; surface Champagne; wet painted; brushed; No matching RAL; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 2700 K;  $\leq 2$  SDCM (initial MacAdam); CRI  $\geq 90$ ; beam angle 30°; degree of protection IP20; Class 1; driver included; light source replaceable by Wever & Ducré or by a professional with explicit authorization; control gear replaceable by end-user;



**LUMINAIRE**

Ceiling \_\_\_\_\_

Surface \_\_\_\_\_

Champagne \_\_\_\_\_

No matching RAL \_\_\_\_\_

IP20 \_\_\_\_\_

Interior \_\_\_\_\_

440 lm \_\_\_\_\_

**LED Module**

2700 K \_\_\_\_\_

CRI  $\geq 90$  \_\_\_\_\_

L80 / 55000h \_\_\_\_\_

$\leq 2$  SDCM (initial MacAdam) \_\_\_\_\_

525 lm \_\_\_\_\_

101 lm/W<sup>a</sup> \_\_\_\_\_

**Optical**

Medium (standard) \_\_\_\_\_

beam angle 30° \_\_\_\_\_

CIE flux code: 93 97 99 100 \_\_\_\_\_

100 \_\_\_\_\_

**Electrical**

phase-cut dim \_\_\_\_\_

220 - 240 V \_\_\_\_\_

system 6.8 W \_\_\_\_\_

Class I \_\_\_\_\_

Standard \_\_\_\_\_

**Physical**

length 70 mm \_\_\_\_\_

width 70 mm \_\_\_\_\_

height 85 mm \_\_\_\_\_


0.25 kg \_\_\_\_\_

**datasheet.quicksum.material**

Aluminium \_\_\_\_\_

<sup>a</sup> Without electrical and optical losses

**LIGHT DISTRIBUTION**



[258154MM3] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.



**Maintenance Factor**

Operating Time [h]	10.000	20.000	30.000	40.000	50.000
LLMF	0.98	0.95	0.93	0.9	0.88
LSF	1	1	1	1	1

MF	$LMF \times RSMF \times LLMF \times LSF$	RSMF <sup>a</sup>	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF <sup>a</sup>	Luminaire Maintenance Factor	LSF	Lamp Survival Factor

<sup>a</sup>According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.