




PROJECT

TYPE


NOTES

QUANTITY

DATE



Oval ceiling recessed downlight made from die-cast aluminium; adjustable; surface White Matt; powder coated, matt texture; RAL 9010; installation without tools using wire springs; suitable for ceiling thickness of 4-23 mm; recessed depth 90 mm; with COB (Chip on Board) technology for maximum efficiency; light colour 3000 K; ≤ 2 SDCM (initial MacAdam); CRI ≥ 90 ; beam angle 56°; 355° rotatable and 35° tiltable; degree of protection IP20; Class 3; IC rated; driver not included; light source replaceable by Wever & Ducré or by a professional with explicit authorization;



LUMINAIRE

Ceiling
Recessed
tilt max 35°
rotation 355°
White Matt
RAL 9010^a
IP20
Interior
1400 lm / 350mA
1880 lm / 500mA

LED Module

3000 K
CRI ≥ 90
L80 / 55000h
 ≤ 2 SDCM (initial MacAdam)
1579 lm / 350mA
132 lm/W^b
12 W^b

Optical

Wide
beam angle 56°
CIE flux code: 89 99 100 100 100

Electrical

excl. driver
17 V
Class III

Physical

length 182 mm
width 94 mm
height 77 mm
0.61 kg
wire springs



Cutout

min. ceiling thickness 4 mm
max. ceiling thickness 23 mm
recessed depth 90 mm
Cut out: 89 x 172-178

^a Colour may deviate slightly due to production conditions

^b Without electrical and optical losses

LIGHT DISTRIBUTION





CONE DIAGRAM

wide 58° 350mA			wide 58° 500mA		
h (m)	E0° (lx)	ø (m)	h (m)	E0° (lx)	ø (m)
1	1510	1.11	1	2020	1.11
2	380	2.23	2	510	2.23
3	170	3.34	3	220	3.34
4	90	4.46	4	130	4.46
5	60	5.57	5	80	5.57

Maintenance Factor

Operating Time [h]	10.000	20.000	30.000	40.000	50.000
LLMF	0.96	0.92	0.88	0.85	0.81
LSF	1	1	1	1	1

MF LMF × RSMF × LLMF × LSF

MF Maintenance Factor

LMF^a Luminaire Maintenance Factor

RSMF^a Room Surface Maintenance Factor

LLMF Lamp Lumens Maintenance Factor

LSF Lamp Survival Factor

^aAccording to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

ELECTRICAL ACCESSORIES

Driver

Type	Colour	Voltage	L·W·H (MM)	Item number
17.5 - 20W			102-51-30	90218601
20W 500mA 26-38V phase-cut dim		26-38V	138-44-30	90224602
20W 500mA 3-40V DALI		3-40V	116-40.5-22	90244604
24W 500mA 6-49V DALI-2		6-49V	143-43-30	90244701

OTHER ACCESSORIES

Metal spring clip

Type	Colour	Voltage	Ø (MM)	Item number
MR16 LED PAR16 max. 12W			59	90019700

Spring clip

Type	Colour	Voltage	Ø (MM)	Item number
MR16 LED PAR16 max. 12W	Black		59	900198B0
MR16 LED PAR16 max. 12W	White		59	900198W0