



PROJECT

TYPE

NOTES

QUANTITY

DATE



Round ceiling recessed downlight made from die-cast aluminium; adjustable; surface Champagne; wet painted, smooth semi glossy; No matching RAL; installation without tools using wire springs; suitable for ceiling thickness of 4-23 mm; recessed depth 65 mm; with COB (Chip on Board) technology for maximum efficiency; light colour 2700 K; ≤ 2 SDCM (initial MacAdam); CRI ≥ 90 ; beam angle 60°; 355° rotatable and 35° tiltable; degree of protection IP20; Class 3; IC rated; driver not included; fits into Kaiser ThermoX® 9320-11; light source replaceable by Wever & Ducré or by a professional with explicit authorization;



LUMINAIRE

Ceiling
Recessed
tilt max 35 °
rotation 355 °
Champagne
No matching RAL
IP20
IC rated
Interior
575 lm / 350mA

LED Module

2700 K
CRI ≥ 90
L70 / 50000h
 ≤ 2 SDCM (initial MacAdam)
635 lm / 350mA
104 lm/W^a
6.1 W^a

Optical

Wide
beam angle 60°
CIE flux code: 91 100 100 100 100

Electrical

excl. driver
17 V
Class III


Physical

diameter 79 mm
height 60 mm
0.05 kg
wire springs

Cutout

diameter 68-70 mm
min. ceiling thickness 4 mm
max. ceiling thickness 23 mm
recessed depth 65 mm

LIGHT DISTRIBUTION



^a Without electrical and optical losses



CONE DIAGRAM

wide 62° 350mA

h (m)	E0° (lx)	ø (m)
1	567	1.21
2	142	2.41
3	63	3.62
4	35	4.83
5	23	6.03

Maintenance Factor

Operating Time [h]	10.000	20.000	30.000	40.000	50.000
LLMF	0.92	0.88	0.83	0.79	0.76
LSF	1	1	1	1	1

MF LMF × RSMF × LLMF × LSF

MF Maintenance Factor

LMF^a Luminaire Maintenance Factor

RSMF^a Room Surface Maintenance Factor

LLMF Lamp Lumens Maintenance Factor

LSF Lamp Survival Factor

^aAccording to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

ELECTRICAL ACCESSORIES

Driver

Type	Colour	Voltage	L·W·H (MM)	Item number
6.3W 350mA 8.6-18V		8.6-18V	66-39-22	90213303
10W 350mA 13-26V phase-cut dim		13-26V	115-41-25	90223406
14W 350mA 10-40V DALI-2 push dim		10-40V	166-29-21	90243502