



PROJECT

---

TYPE

---

NOTES

---

QUANTITY


---

DATE

---



Round ceiling recessed downlight made from die-cast aluminium; surface Black Matt; powder coated, matt texture; RAL 9011; installation without tools using wire springs; suitable for ceiling thickness of 4-38 mm; recessed depth 100 mm; lamp socket GU5.3; lamp type QR-CBC51; max. 12W; 12 V; degree of protection IP20; Class 3; driver not included; lamp not included;



**General**

Ceiling  
 Recessed  
 Black Matt  
 RAL 9011 <sup>a</sup>  
 IP20  
 Interior

**LED**

lamp QR-CBC51  
 socket GU5.3  
 max. per socket 12.0 W

**Electrical**

excl. driver  
 12 V  
 Class III  
 Standard

**Physical**

diameter 84 mm  
 height 86 mm  
 0.11 kg  
 blade springs

**Cutout**

diameter 76-79 mm  
 min. ceiling thickness 4 mm  
 max. ceiling thickness 38 mm  
 recessed depth 100 mm

**datasheet.quicksum.material**

Aluminium

<sup>a</sup> Colour may deviate slightly due to production conditions



**ELECTRICAL ACCESSORIES**

**Driver**

Type	Colour	Voltage	L·W·H (MM)	Item number
10W   12V   3-10VA   phase-cut dim		3-10VA	102-51-30	90221401
25W   12V   8-25VA   phase-cut dim		8-25VA	145-51-30	90221701