





**PROJECT**
**TYPE**
**NOTES**
**QUANTITY**
**DATE**


Cylindrical ceiling surface mounted downlight made from die-cast aluminium; adjustable; surface Black Matt + Gold; wet painted, matt smooth; RAL 9011; with COB (Chip on Board) technology for maximum efficiency; DALI dim; light colour 3000 K;  $\leq 2$  SDCM (initial MacAdam); CRI  $\geq 90$ ; beam angle 15°; 355° rotatable and 25° tiltable; degree of protection IP20; Class I; driver included; light source replaceable by Wever & Ducré or by a professional with explicit authorization; control gear replaceable by end-user;


**LUMINAIRE**

Ceiling  
Surface  
tilt max 25 °  
rotation 355 °  
Black Matt + Gold  
RAL 9011 <sup>a</sup>  
IP20  
Interior  
875 lm

**LIGHT DISTRIBUTION**

**LED Module**

3000 K  
CRI  $\geq 90$   
L80 / 50000h  
 $\leq 2$  SDCM (initial MacAdam)  
1060 lm  
121 lm/W <sup>b</sup>

**Optical**

Narrow  
beam angle 15°  
CIE flux code: 88 99 100 100  
100

**Electrical**

DALI-2  
220 - 240 V  
system 12.2 W  
Class I  
Standard

**Physical**

diameter 100 mm  
height 130 mm  
0.65 kg

**[datasheet](#).[quicksum](#).[material](#)**

Aluminium

<sup>a</sup> Colour may deviate slightly due to production conditions

<sup>b</sup> Without electrical and optical losses


**CONE DIAGRAM**

narrow 16°

h (m)	E0° (lx)	Ø (m)
1	4370	0.28
2	1090	0.55
3	490	0.83
4	270	1.11
5	170	1.39

**Maintenance Factor**

Operating Time [h]	10.000	20.000	30.000	40.000	50.000
LLMF	0.96	0.92	0.88	0.85	0.81
LSF	1	1	1	1	1

MF	LMF × RSMF × LLMF × LSF	RSMF <sup>a</sup>	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMFa	Luminaire Maintenance Factor	LSF	Lamp Survival Factor

<sup>a</sup>According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

**OTHER ACCESSORIES**
**Metal spring clip**

Type	Colour	Voltage	Ø (MM)	Item number
MR16   LED   PAR16   max. 12W			59	90019700

**Spring clip**

Type	Colour	Voltage	Ø (MM)	Item number
MR16   LED   PAR16   max. 12W	Black		59	900198BO
MR16   LED   PAR16   max. 12W	Gold		59	900198GO
MR16   LED   PAR16   max. 12W	Champagne		59	900198MO
MR16   LED   PAR16   max. 12W	Bronze		59	900198QO
MR16   LED   PAR16   max. 12W	Silver		59	900198SO
MR16   LED   PAR16   max. 12W	White		59	900198WO