



**PROJECT** \_\_\_\_\_

---

**TYPE** \_\_\_\_\_

---

**NOTES** \_\_\_\_\_


---

**QUANTITY** \_\_\_\_\_


---

**DATE** \_\_\_\_\_

---



Squared ceiling recessed downlight made from die-cast aluminium; surface White Matt; powder coated, matt texture; RAL 9010; installation without tools using wire springs; suitable for ceiling thickness of 4-30 mm; recessed depth 90 mm; with COB (Chip on Board) technology for maximum efficiency; light colour 3000 K;  $\leq 2$  SDCM (initial MacAdam); CRI  $\geq 90$ ; beam angle 15°; degree of protection from below IP44; from above IP20; Class 3; driver not included; light source replaceable by Wever & Ducré or by a professional with explicit authorization;



**LUMINAIRE**

Ceiling \_\_\_\_\_  
 Recessed \_\_\_\_\_  
 White Matt \_\_\_\_\_  
 RAL 9010 <sup>a</sup> \_\_\_\_\_  
 front IP44 \_\_\_\_\_  
 back IP20 \_\_\_\_\_  
 Interior \_\_\_\_\_  
 600 lm / 350mA \_\_\_\_\_  
 810 lm / 500mA \_\_\_\_\_

**LED Module**

3000 K \_\_\_\_\_  
 CRI  $\geq 90$  \_\_\_\_\_  
 L80 / 55000h \_\_\_\_\_  
 $\leq 2$  SDCM (initial MacAdam) \_\_\_\_\_  
 790 lm / 350mA \_\_\_\_\_  
 132 lm/W <sup>b</sup> \_\_\_\_\_  
 6 W <sup>b</sup> \_\_\_\_\_

**Optical**

Narrow \_\_\_\_\_  
 beam angle 15° \_\_\_\_\_  
 CIE flux code: 95 100 100 100 \_\_\_\_\_  
 100 \_\_\_\_\_

**Electrical**

excl. driver \_\_\_\_\_  
 17 V \_\_\_\_\_  
 Class III \_\_\_\_\_  
 Standard \_\_\_\_\_

**Physical**

length 85 mm \_\_\_\_\_  
 width 85 mm \_\_\_\_\_  
 height 89 mm \_\_\_\_\_  
 0.21 kg \_\_\_\_\_  
 wire springs \_\_\_\_\_

**Cutout**



length 76 mm \_\_\_\_\_  
 width 78 mm \_\_\_\_\_  
 min. ceiling thickness 4 mm \_\_\_\_\_  
 max. ceiling thickness 30 mm \_\_\_\_\_  
 recessed depth 90 mm \_\_\_\_\_

**datasheet.quicksum.material**

Aluminium \_\_\_\_\_

<sup>a</sup> Colour may deviate slightly due to production conditions  
<sup>b</sup> Without electrical and optical losses

**LIGHT DISTRIBUTION**





**CONE DIAGRAM**

narrow 16° 350mA			narrow 16° 500mA		
h (m)	E0° (lx)	ø (m)	h (m)	E0° (lx)	ø (m)
1	3280	0.28	1	4410	0.28
2	820	0.56	2	1100	0.56
3	360	0.84	3	490	0.84
4	200	1.12	4	280	1.12
5	130	1.41	5	180	1.41

**Maintenance Factor**

Operating Time [h]	10.000	20.000	30.000	40.000	50.000
LLMF	0.96	0.92	0.88	0.85	0.81
LSF	1	1	1	1	1

MF	$LMF \times RSMF \times LLMF \times LSF$	RSMF <sup>a</sup>	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF <sup>a</sup>	Luminaire Maintenance Factor	LSF	Lamp Survival Factor

<sup>a</sup>According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

**ELECTRICAL ACCESSORIES**

**Driver**

Type	Colour	Voltage	L·W·H (MM)	Item number
10W   500mA   13-20V		13-20V	60-39-20	90214406
10W   500mA   12-21V   phase-cut dim		12-21V	115-41-25	90224403
15W   500mA   10-31V   DALI-2 push dim		10-31V	166-29-21	90244501