



25825LBQ9

| PROJECT | |
|----------|--|
| ТҮРЕ | |
| NOTES | |
| QUANTITY | |





DATE



Cylindrical ceiling surface mounted downlight made from die-cast aluminium; surface Black Matt + Bronze; RAL 9011; with COB (Chip on Board) technology for maximum efficiency; light colour 1800 - 3000 K colour warm dimming; CRI \geq 90; beam angle 38°; degree of protection IP20; Class 3; driver included; light source replaceable by Wever & Ducré or by a professional with explicit authorization;

General

| Ceiling |
|-----------------------|
| Surface |
| Black Matt + Bronze |
| RAL 9011 ^a |
| IP20 |
| Interior |
| 450 lm |
| |

LED

| colour warm dimming | |
|----------------------------|---|
| 1800 - 3000 K | |
| CRI ≥ 90 | |
| ≤ 2 SDCM (initial MacAdam) | _ |
| | 7 |

Optical

| Medium (standard) | |
|-------------------|--|
| beam angle 38° | |

Electrical

| excl. power supply |
|--------------------|
| 24 V |
| system 7.0 W |
| Class III |

Physical

| diameter 70 mm | |
|----------------|--|
| height 82 mm | |
| 0.24 kg | |

^a Colour may deviate slightly due to production conditions

