




PROJECT

TYPE

NOTES

QUANTITY

DATE



Cone shaped ceiling suspended luminaire made from aluminium; surface Cement Grey + White Matt wet painted; matt texture; RAL 7033; inclusive black adjustable cable suspension max. 4000mm; PCB 3-step binning; light colour 1800 - 3000 K colour warm dimming; CRI ≥ 90; 24 V; degree of protection IP20; Class 3; ceiling base included; Loxone ready; light source replaceable by Wever & Ducré or by a professional with explicit authorization;

General

Ceiling _____
 Suspended _____
 Cement Grey + White Matt _____
 RAL 7033 ^a _____
 IP20 _____
 Interior _____
 750 lm _____

LED

colour warm dimming _____
 1800 - 3000 K _____
 CRI ≥ 90 _____
 L80 / 55000h _____
 ≤ 3 SDCM (initial MacAdam) _____

Electrical

excl. driver _____
 24 V _____
 system 12.0 W _____
 Class III _____
 Standard _____


Physical

diameter 760 mm _____
 height 235 mm _____
 5.5 kg _____

datasheet.quicksum.material

Aluminium _____

^a Colour may deviate slightly due to production conditions



[‘25538LGW9’] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.