



**PROJECT**

---

**TYPE**

---

**NOTES**


---

**QUANTITY**

---

**DATE**

---



Cone shaped ceiling suspended luminaire made from aluminium; surface Cement Grey + White Matt wet painted; matt texture; RAL 7033; inclusive black adjustable cable suspension max. 4000mm; PCB 3-step binning; light colour 1800 - 3000 K colour warm dimming; CRI  $\geq 90$ ; 24 V; degree of protection IP20; Class 3; ceiling base included; Loxone ready; light source replaceable by Wever & Ducré or by a professional with explicit authorization;

**General**

Ceiling \_\_\_\_\_  
 Suspended \_\_\_\_\_  
 Cement Grey + White Matt \_\_\_\_\_  
 RAL 7033 <sup>a</sup> \_\_\_\_\_  
 IP20 \_\_\_\_\_  
 Interior \_\_\_\_\_  
 750 lm \_\_\_\_\_

**LED**

colour warm dimming \_\_\_\_\_  
 1800 - 3000 K \_\_\_\_\_  
 CRI  $\geq 90$  \_\_\_\_\_  
 L80 / 55000h \_\_\_\_\_  
 $\leq 3$  SDCM (initial MacAdam) \_\_\_\_\_

**Electrical**

excl. driver \_\_\_\_\_  
 24 V \_\_\_\_\_  
 system 12.0 W \_\_\_\_\_  
 Class III \_\_\_\_\_  
 Standard \_\_\_\_\_


**Physical**

diameter 380 mm \_\_\_\_\_  
 height 460 mm \_\_\_\_\_  
 2.74 kg \_\_\_\_\_

**datasheet.quicksum.material**

Aluminium \_\_\_\_\_

<sup>a</sup> Colour may deviate slightly due to production conditions



[‘25518LGW9’] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.