




PROJECT

TYPE


NOTES

QUANTITY

DATE



Squared ceiling recessed downlight made from die-cast aluminium; adjustable; surface Black Matt; powder coated, matt texture; RAL 9011; installation without tools using wire springs; suitable for ceiling thickness of 4-25 mm; recessed depth 75 mm; with COB (Chip on Board) technology for maximum efficiency; light colour 1800 - 3000 K colour warm dimming; CRI ≥ 90 ; beam angle 38°; 355° rotatable and 60° tiltable; degree of protection IP20; Class 3; IC rated; driver included; light source replaceable by Wever & Ducré or by a professional with explicit authorization;



General

Ceiling
Recessed
tilt max 60 °
rotation 355 °
Black Matt
RAL 9011 ^a
IP20
Interior

LED

colour warm dimming
1800 - 3000 K
CRI ≥ 90
 ≤ 2 SDCM (initial MacAdam)

Optical

Medium (standard)
beam angle 38°

Electrical

excl. power supply
24 V
Class III

Physical

length 62 mm
width 120 mm
height 96 mm
0.47 kg
wire springs

Cutout

length 111 mm
width 111 mm
min. ceiling thickness 4 mm
max. ceiling thickness 25 mm
recessed depth 75 mm

^a Colour may deviate slightly due to production conditions