



PROJECT

TYPE

NOTES

QUANTITY

DATE



Cylindrical ceiling suspended luminaire made from die-cast aluminium; surface Black Matt; powder coated; matt texture; RAL 9011; with COB (Chip on Board) technology for maximum efficiency; 350 mA; light colour 3000 K; ≤ 2 SDCM (initial MacAdam); CRI ≥ 90 ; beam angle 75°; 18 V; degree of protection IP20; Class 3; to be combined with single or multi ceiling base (including phase-cut dim driver); light source replaceable by Wever & Ducré or by a professional with explicit authorization;

LUMINAIRE

Ceiling
Suspended
Black Matt
RAL 9011 ^a
IP20
Interior
565 lm

LED Module

3000 K
CRI ≥ 90
L80 / 50000h
 ≤ 2 SDCM (initial MacAdam)
575 lm
139 lm/W ^b

Optical

Wide
beam angle 75°

Electrical


excl. driver
18 V
Class III

Physical

diameter 43 mm
height 500 mm
0.48 kg
cable length 4000 mm

^a Colour may deviate slightly due to production conditions

^b Without electrical and optical losses





MOUNTING ACCESSORIES

Hook long

Type	Colour	Voltage	Ø-H (MM)	Item number
for cable 4.25-5.5mm diameter	White		15-49	90052083
for cable 4.25-5.5mm diameter	Black		15-49	90052084

Linear multi base 2.3

Type	Colour	Voltage	L·W·H (MM)	Item number
3 luminaires	Black		600·34·52	914133B0
3 luminaires	White		600·34·52	914133W0

Linear multi base 2.6

Type	Colour	Voltage	L·W·H (MM)	Item number
6 luminaires	Black		1200·34·52	914134B0
6 luminaires	White		1200·34·52	914134W0

Linear multi base 2.9

Type	Colour	Voltage	L·W·H (MM)	Item number
9 luminaires	Black		1800·34·52	914135B0
9 luminaires	White		1800·34·52	914135W0

Multi chandelier

Type	Colour	Voltage	Ø·H (MM)	Item number
3 luminaires wide slots	Black		380·44	914124BB0
3 luminaires wide slots	Black + Bronze		380·44	914124BQ0
3 luminaires wide slots	White		380·44	914124WW0
6 luminaires wide slots	Black		380·44	914125BB0
6 luminaires wide slots	Black + Bronze		380·44	914125BQ0
6 luminaires wide slots	White		380·44	914125WW0

Semi recessed base round

Type	Colour	Voltage	Ø·H (MM)	Item number
incl. driver 350 mA	Black		84·72	914152B0
incl. driver 350 mA	White		84·72	914152W0

Single base round

Type	Colour	Voltage	Ø·H (MM)	Item number
incl. driver	Black		83·39	914112B0
incl. driver	Bronze		83·39	914112Q0
incl. driver	White		83·39	914112W0