



PROJECT

TYPE


NOTES

QUANTITY

DATE



Cylindrical ceiling suspended luminaire made from die-cast aluminium; surface Live Simple; RAL 090 9005; with COB (Chip on Board) technology for maximum efficiency; 350 mA; light colour 3000 K; ≤ 2 SDCM (initial MacAdam); CRI ≥ 90 ; beam angle 75°; 18 V; degree of protection IP20; Class 3; to be combined with single or multi ceiling base (including phase-cut dim driver); light source replaceable by Wever & Ducré or by a professional with explicit authorization;



LUMINAIRE

Ceiling
Suspended
Live Simple
RAL 090 9005 ^a
IP20
Interior
565 lm

LED Module

3000 K
CRI ≥ 90
L80 / 50000h
 ≤ 2 SDCM (initial MacAdam)
575 lm
139 lm/W ^b

Optical

Wide
beam angle 75°

Electrical

excl. driver
18 V
Class III

Physical

diameter 43 mm
height 300 mm
0.33 kg
cable length 4000 mm

^a Colour may deviate slightly due to production conditions

^b Without electrical and optical losses



MOUNTING ACCESSORIES

Hook long

Type	Colour	Voltage	Ø-H (MM)	Item number
for cable 4.25-5.5mm diameter	White		15-49	90052083
for cable 4.25-5.5mm diameter	Black		15-49	90052084

Linear multi base 2.3

Type	Colour	Voltage	L·W·H (MM)	Item number
3 luminaires	Black		600·34·52	914133B0
3 luminaires	White		600·34·52	914133W0

Linear multi base 2.6

Type	Colour	Voltage	L·W·H (MM)	Item number
6 luminaires	Black		1200·34·52	914134B0
6 luminaires	White		1200·34·52	914134W0

Linear multi base 2.9

Type	Colour	Voltage	L·W·H (MM)	Item number
9 luminaires	Black		1800·34·52	914135B0
9 luminaires	White		1800·34·52	914135W0

Multi chandelier

Type	Colour	Voltage	Ø-H (MM)	Item number
3 luminaires wide slots	Black		380·44	914124BB0
3 luminaires wide slots	Black + Bronze		380·44	914124BQ0
3 luminaires wide slots	White		380·44	914124WW0
6 luminaires wide slots	Black		380·44	914125BB0
6 luminaires wide slots	Black + Bronze		380·44	914125BQ0
6 luminaires wide slots	White		380·44	914125WW0

Semi recessed base round

Type	Colour	Voltage	Ø-H (MM)	Item number
incl. driver 350 mA	Black		84·72	914152B0
incl. driver 350 mA	White		84·72	914152W0

Single base round

Type	Colour	Voltage	Ø-H (MM)	Item number
incl. driver	Black		83·39	914112B0
incl. driver	Bronze		83·39	914112Q0
incl. driver	White		83·39	914112W0