



PROJECT

TYPE

NOTES

QUANTITY

DATE



Cylindrical ceiling suspended luminaire made from die-cast aluminium; surface Live Simple; RAL 090 9005; lamp socket GU10; lamp type PAR11; max. 12W; 100 - 240 V; degree of protection IP20; Class I; lamp not included; to be combined with single or multi ceiling base (including phase-cut dim driver); light source replaceable by Wever & Ducré or by a professional with explicit authorization;

General

Ceiling
Suspended
Live Simple
RAL 090 9005 ^a
IP20
Interior
405 lm

LED

lamp PAR11
socket GU10
max. per socket 12.0 W
2700 K
CRI ≥ 90


Electrical

100 - 240 V
system 5.5 W
Class I

Physical

diameter 43 mm
height 300 mm
0.4 kg
cable length 4000 mm

^a Colour may deviate slightly due to production conditions





MOUNTING ACCESSORIES

Cable Wall-Ceiling Bracket

Type	Colour	Voltage	Ø-H (MM)	Item number
	White		16-30	90019197
	Black		16-30	90019198

Hook long

Type	Colour	Voltage	Ø-H (MM)	Item number
for cable 4.25-5.5mm diameter	White		15-49	90052083
for cable 4.25-5.5mm diameter	Black		15-49	90052084

Invisible ceiling base

Type	Colour	Voltage	L-W (MM)	Item number
	Black		140-66	90015195
	White		140-66	90015196

Linear multi base 2.3

Type	Colour	Voltage	L-W-H (MM)	Item number
3 luminaires	Black		600-34-52	914133B0
3 luminaires	White		600-34-52	914133W0

Linear multi base 2.6

Type	Colour	Voltage	L-W-H (MM)	Item number
6 luminaires	Black		1200-34-52	914134B0
6 luminaires	White		1200-34-52	914134W0

Linear multi base 2.9

Type	Colour	Voltage	L-W-H (MM)	Item number
9 luminaires	Black		1800-34-52	914135B0
9 luminaires	White		1800-34-52	914135W0

Multi chandelier

Type	Colour	Voltage	Ø-H (MM)	Item number
9 luminaires	Black		380-44	914120BB0
9 luminaires	Black + Bronze		380-44	914120BQ0
9 luminaires	White		380-44	914120WW0

Multiple base linear

Type	Colour	Voltage	L-W-H (MM)	Item number
up to max. 2 luminaires	White		600-30-45	90052007
up to max. 2 luminaires	Black		600-30-45	90052008
up to max. 3 luminaires	White		900-30-45	90052009
up to max. 3 luminaires	Black		900-30-45	90052010
up to max. 4 luminaires	White		1200-30-45	90052011
up to max. 4 luminaires	Black		1200-30-45	90052012
up to max. 5 luminaires	White		1500-30-45	90052013
up to max. 5 luminaires	Black		1500-30-45	90052014

Multiple base round

Type	Colour	Voltage	Ø-H (MM)	Item number
up to max. 4 luminaires	White		123-44	90052005
up to max. 4 luminaires	Black		123-44	90052006
up to max. 8 luminaires	White		123-44	90052031
up to max. 8 luminaires	Black		123-44	90052032

['260120LS0'] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.


Semi recessed base round

Type	Colour	Voltage	Ø·H (MM)	Item number
for shades without steel wire only	White		84-72	90052026
for shades without steel wire only	Black		84-72	90052027

Single base round

Type	Colour	Voltage	Ø·H (MM)	Item number
excl. driver	Black		83-39	914110B0
excl. driver	Bronze		83-39	914110Q0
excl. driver	White		83-39	914110W0

Wall Base

Type	Colour	Voltage	Ø·H (MM)	Item number
for 1 luminaire	White		82-32	90019195
for 1 luminaire	Black		82-32	90019196

LAMPS
PAR11 LED Lamp

Type	Colour	Voltage	Ø·H (MM)	Item number
2700K >90 CRI GU10	Black		34-56	901128B3
3000K >90 CRI GU10	Black		34-56	901128B5
2700K >90 CRI GU10	White		34-56	901128W3
3000K >90 CRI GU10	White		34-56	901128W5