WEVER & DUCRÉ LIGHTING

LECA snooze SEMI-RECESSED 1.0

188544W3

PROJECT

TYPE

NOTES

QUANTITY

DATE





Bedside semi-recessed luminaire made from die-cast aluminium with round base; surface White Matt; RAL 9010; inclusive on/off switch in white; with COB (Chip on Board) technology for maximum efficiency; light colour 2700 K; CRI ≥ 90; beam angle 17°; 220 - 240 V; 350° rotatable and 90° tiltable; degree of protection IP20; Class 1; inclusive USB-C port; driver included; installation box is not included and not required; compatible with standard Ø68 mm installation boxes; inclusive honeycomb louver, to reduce glare; light source replaceable by Wever & Ducré or by a professional with explicit authorization; control gear replaceable by end-user;



LUMINAIRE

Wall
Semi-Recessed
tilt max 90 °
rotation 350 °
White Matt
RAL 9010 [a]
IP20
Interior
240 lm

LED MODULE

2700 K
CRI ≥ 90
L80 / 50000h

OPTICAL

Narrow
beam angle 17°

ELECTRICAL

incl. driver | incl. switch on/off | push dim
220 - 240 V
system 5.0 W
Class I

PHYSICAL

diameter 62 mm
height 62 mm
0.45 kg

CUTOUT

diameter 68-71 mm
min. ceiling thickness 5 mm
max. ceiling thickness 40 mm
recessed depth 36 mm

[a] Colour may deviate slightly due to production conditions

['188544W3'] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.
© Wever & Ducré BV · Spinnerijstraat 99/21 · 8500 Kortrijk · Belgium · www.weverducre.com