WEVER & DUCRÉ LIGHTING

TAPE 8.0

722474D5

PROJECT

TYPE

NOTES

QUANTITY

DATE



IP65

Floor surface mounted luminaire made from die-cast aluminium; surface Grey Texture; powder coated; matt texture; RAL 9007; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 3000 K; ≤ 3 SDCM (initial MacAdam); CRI ≥ 90; 220 - 240 V; degree of protection IP65; Class 1; optional ground spike available; driver included; light source not replaceable; control gear replaceable by end-user;



LUMINAIRE

Floor
Surface
Grey Texture
RAL 9007 [a]
IP65
Exterior
425 lm

LED MODULE

3000 K
CRI ≥ 90
L80 / 100000 h
≤ 3 SDCM (initial MacAdam)

OPTICAL

Indirect
CIE flux code: 53 89 99 98 100

ELECTRICAL

phase-cut dim
220 - 240 V
system 7.8 W
Class I

PHYSICAL

length 180 mm
width 60 mm
height 800 mm
3.1 kg

[a] Colour may deviate slightly due to production conditions

LIGHT DISTRIBUTION



Maintenance Factor

Operating Time [h]	10.000	20.000	30.000	40.000	50.000
LLMF	0.98	0.98	0.98	0.97	0.97
LSF	1	1	1	1	1

MF	LMF × RSMF × LLMF × LSF
MF	Maintenance Factor
LMF[a]	Luminaire Maintenance Factor
RSMF[a]	Room Surface Maintenance Factor
LLMF	Lamp Lumens Maintenance Factor
LSF	Lamp Survival Factor

[a]According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

BASE

GROUND SPIKE

TYPE	COLOUR	VOLTAGE	L·W·H (MM)	ITEM NUMBER
TAPE			62·115·357	90013102

['722474D5'] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.
© Wever & Ducré BV · Spinnerijstraat 99/21 · 8500 Kortrijk · Belgium · www.weverducre.com