



**PROJECT**

**TYPE**


**NOTES**

**QUANTITY**

**DATE**



Floor surface mounted luminaire made from die-cast aluminium; surface Grey Texture; powder coated; matt texture; RAL 9007; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 3000 K;  $\leq 3$  SDCM (initial MacAdam); CRI  $\geq 90$ ; 220 - 240 V; degree of protection IP65; Class I; optional ground spike available; driver included; light source not replaceable; control gear replaceable by end-user;



**LUMINAIRE**

Floor  
Standing  
Grey Texture  
RAL 9007<sup>a</sup>  
IP65  
Exterior  
425 lm

**LED Module**

3000 K  
CRI  $\geq 90$   
L80 / 100000 h  
 $\leq 3$  SDCM (initial MacAdam)

**Optical**

Indirect  
CIE flux code: 53 89 99 98 100

**Electrical**


phase-cut dim  
220 - 240 V  
system 7.8 W  
Class I

**Physical**

length 180 mm  
width 60 mm  
height 800 mm  
3.1 kg

<sup>a</sup> Colour may deviate slightly due to production conditions

**LIGHT DISTRIBUTION**





## Maintenance Factor

Operating Time [h]	10.000	20.000	30.000	40.000	50.000
LLMF	0.98	0.98	0.98	0.97	0.97
LSF	1	1	1	1	1

MF LMF × RSMF × LLMF × LSF

MF Maintenance Factor

LMF<sup>a</sup> Luminaire Maintenance Factor

RSMF<sup>a</sup> Room Surface Maintenance Factor

LLMF Lamp Lumens Maintenance Factor

LSF Lamp Survival Factor

<sup>a</sup>According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

## BASE

### Ground Spike

Type	Colour	Voltage	L·W·H (MM)	Item number
TAPE			62·115·357	90013102