

TAPE 6.0

722374D5

GENERAL

Floor , Standing
Grey Texture
RAL 9007 ^a
IP65
Exterior
Output: 425 lm
CIE flux code: 53 89 99 98 100

LED

3000 K
CRI ≥ 90
L80 / 60000 h
3 SDCM

ELECTRICAL

phase-cut dim
220 - 240 V
Total connected power 7.8 W
Class 1

PHYSICAL

Length 180 mm
Width 60 mm
Height 600 mm
2.42 kg

^a Color may deviate slightly due to production conditions.


Project _____

Type _____


Notes _____

Quantity _____


Date _____



Floor surface mounted luminaire made from die-cast aluminium; surface Grey Texture; powder coated; matt texture; RAL 9007; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; 220 - 240 V; degree of protection IP65; PC1; optional ground spike available; driver included; light source not replaceable; control gear replaceable by end-user;



LIGHT DISTRIBUTION



TAPE

6.0

722374D5

Maintenance Factors

| Operating Time [h] | 10 000 | 20 000 | 30 000 | 40 000 | 50 000 |
|--------------------|--------|--------|--------|--------|--------|
| LLMF | 0.98 | 0.98 | 0.98 | 0.97 | 0.97 |
| LSF | 1 | 1 | 1 | 1 | 1 |

| | | | | |
|------------------|------------------------------|--|-------------------|---------------------------------|
| MF | LMF × RSMF × LLMF × LSF | | RSMF ^a | Room Surface Maintenance Factor |
| MF | Maintenance Factor | | LLMF | Lamp Lumens Maintenance Factor |
| LMF ^a | Luminaire Maintenance Factor | | LSF | Lamp Survival Faktor |

^a According to “CIE 97, Maintenance of indoor electric lighting systems”, 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

MOUNTING

Ground Spike

| TYPE | L · W · H (MM) | ORDERCODE |
|------|----------------|-----------------|
| TAPE | 62-115-357 | 9 0 0 1 3 1 0 2 |