



**PROJECT** \_\_\_\_\_

**TYPE** \_\_\_\_\_


**NOTES** \_\_\_\_\_

**QUANTITY** \_\_\_\_\_

**DATE** \_\_\_\_\_



Floor surface mounted luminaire made from die-cast aluminium; surface Grey Texture; powder coated; matt texture; RAL 9007; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 3000 K;  $\leq 3$  SDCM (initial MacAdam); CRI  $\geq 90$ ; 220 - 240 V; degree of protection IP65; Class I; optional ground spike available; driver included; light source not replaceable; control gear replaceable by end-user;



**LUMINAIRE**

Floor \_\_\_\_\_

Standing \_\_\_\_\_

Grey Texture \_\_\_\_\_

RAL 9007 <sup>a</sup> \_\_\_\_\_

IP65 \_\_\_\_\_

Exterior \_\_\_\_\_

425 lm \_\_\_\_\_

**LED Module**

3000 K \_\_\_\_\_

CRI  $\geq 90$  \_\_\_\_\_

L80 / 100000 h \_\_\_\_\_

$\leq 3$  SDCM (initial MacAdam) \_\_\_\_\_

**Optical**

Indirect \_\_\_\_\_

CIE flux code: 53 89 99 98 100 \_\_\_\_\_

**Electrical**

phase-cut dim \_\_\_\_\_

220 - 240 V \_\_\_\_\_

system 7.8 W \_\_\_\_\_

Class I \_\_\_\_\_

Standard \_\_\_\_\_

**Physical**

length 180 mm \_\_\_\_\_

width 60 mm \_\_\_\_\_

height 600 mm \_\_\_\_\_


2.42 kg \_\_\_\_\_

**datasheet.quicksum.material**

Aluminium \_\_\_\_\_

<sup>a</sup> Colour may deviate slightly due to production conditions

**LIGHT DISTRIBUTION**



[722374D5] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.



**Maintenance Factor**

Operating Time [h]	10.000	20.000	30.000	40.000	50.000
LLMF	0.98	0.98	0.98	0.97	0.97
LSF	1	1	1	1	1

MF	$LMF \times RSMF \times LLMF \times LSF$	RSMF <sup>a</sup>	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF <sup>a</sup>	Luminaire Maintenance Factor	LSF	Lamp Survival Factor

<sup>a</sup>According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

**BASE**

**Ground Spike**

Type	Colour	Voltage	L·W·H (MM)	Item number
TAPE			62-115-357	90013102