

# TAPE 4.0

722274D5

## GENERAL

Floor , Standing  
Grey Texture  
RAL 9007 <sup>a</sup>  
IP65  
Exterior  
Output: 425 lm  
CIE flux code: 53 89 99 98 100

## LED

3000 K  
CRI ≥ 90  
L80 / 60000 h  
3 SDCM

## ELECTRICAL

phase-cut dim  
220 - 240 V  
Total connected power 7.8 W  
Class 1

## PHYSICAL

Length 180 mm  
Width 60 mm  
Height 400 mm  
1.82 kg

<sup>a</sup> Color may deviate slightly due to production conditions.

Project \_\_\_\_\_

Type \_\_\_\_\_


Notes \_\_\_\_\_

Quantity \_\_\_\_\_


Date \_\_\_\_\_



Floor surface mounted luminaire made from die-cast aluminium; surface Grey Texture; powder coated; matt texture; RAL 9007; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; 220 - 240 V; degree of protection IP65; PC1; optional ground spike available; driver included; light source not replaceable; control gear replaceable by end-user;



## LIGHT DISTRIBUTION



TAPE

4.0

722274D5

Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.98	0.98	0.98	0.97	0.97
LSF	1	1	1	1	1

MF	$LMF \times RSMF \times LLMF \times LSF$	RSMF <sup>a</sup>	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF <sup>a</sup>	Luminaire Maintenance Factor	LSF	Lamp Survival Faktor

<sup>a</sup> According to “CIE 97, Maintenance of indoor electric lighting systems”, 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

MOUNTING

Ground Spike

TYPE	L · W · H (MM)	ORDERCODE
TAPE	62-115-357	9 0 0 1 3 1 0 2