

TAPE 1.0

722174D5

GENERAL

Wall , Surface

Grey Texture

RAL 9007 ^a

IP65

Exterior

Indirect 215 lm

Direct 215 lm

Total 430 lm

CIE flux code: 12 45 84 50 100

LED

3000 K

CRI \geq 90

L80 / 60000 h

3 SDCM

ELECTRICAL

phase-cut dim

220 - 240 V

Total connected power 7.8 W

Class 1

PHYSICAL

Length 180 mm

Width 180 mm

Height 60 mm

0.73 kg

^a Color may deviate slightly due to production conditions.


Project

Type


Notes

Quantity


Date



Rectangular wall surface luminaire made from aluminium; rounded edges; surface Grey Texture; powder coated; matt texture; RAL 9007; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 3000 K; binning initial MacAdam \leq 3 SDCM; CRI \geq 90; 220 - 240 V; degree of protection IP65; PC1; driver included; light source not replaceable; control gear replaceable by end-user;



LIGHT DISTRIBUTION



TAPE
1.0

722174D5

Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.98	0.98	0.98	0.97	0.97
LSF	1	1	1	1	1

MF	LMF × RSMF × LLMF × LSF		RSMF ^a	Room Surface Maintenance Factor	
MF	Maintenance Factor		LLMF	Lamp Lumens Maintenance Factor	
LMF ^a	Luminaire Maintenance Factor		LSF	Lamp Survival Faktor	

^a According to “CIE 97, Maintenance of indoor electric lighting systems”, 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.