



PROJECT _____

TYPE _____


NOTES _____

QUANTITY _____

DATE _____



Rectangular wall surface luminaire made from aluminium; rounded edges; surface Grey Texture; powder coated; matt texture; RAL 9007; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 3000 K; ≤ 3 SDCM (initial MacAdam); CRI ≥ 90 ; 220 - 240 V; degree of protection IP65; Class I; driver included; light source not replaceable; control gear replaceable by end-user;



LUMINAIRE

Wall
Surface
Grey Texture
RAL 9007 ^a
IP65
Exterior
425 lm

LED Module

3000 K
CRI ≥ 90
L80 / 100000 h
≤ 3 SDCM (initial MacAdam)

Optical

Indirect
CIE flux code: 12 45 84 50 100

Electrical

phase-cut dim
220 - 240 V
system 7.8 W
Class I
Standard

Physical


length 180 mm
width 180 mm
height 60 mm
0.73 kg

datasheet.quicksum.material

Aluminium

^a Colour may deviate slightly due to production conditions

LIGHT DISTRIBUTION



[722174D5] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.



Maintenance Factor

Operating Time [h]	10.000	20.000	30.000	40.000	50.000
LLMF	0.98	0.98	0.98	0.97	0.97
LSF	1	1	1	1	1

MF	$LMF \times RSMF \times LLMF \times LSF$	RSMF ^a	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF ^a	Luminaire Maintenance Factor	LSF	Lamp Survival Factor

^aAccording to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.