



PROJECT

TYPE

NOTES

QUANTITY

DATE



Cylindrical wall surface mounted luminaire made from aluminium; surface White Matt; powder coated; matt texture; RAL 9010; direct/indirect light distribution; PCB 3-step binning; light colour 1800 - 3000 K colour warm dimming; CRI ≥ 90; 24 V; degree of protection IP65; Class 3; inclusive flaps for adjustable beam angle; light source replaceable by Wever & Ducré or by a professional with explicit authorization;



General

Wall
 Surface
 White Matt
 RAL 9010 ^a
 IP65
 Exterior
 total 650 lm

LED

colour warm dimming
 indirect: 2700 K
 1800 - 3000 K
 CRI ≥ 90
 L80 / 55000h

Optical

Variable

Electrical

excl. driver
 24 V
 system 11.0 W
 Class III
 Standard

Physical

diameter 150 mm
 height 160 mm
 0.53 kg

datasheet.quicksum.material

Aluminium

^a Colour may deviate slightly due to production conditions

[74924LW9] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.