



PROJECT

---

TYPE

---

NOTES

---

QUANTITY

---

DATE

---



Ceiling suspended luminaire made from aluminium; surface Black Matt + Gold wet painted; matt texture; inclusive adjustable cable suspension max. 4000mm in Signal Black; with COB (Chip on Board) technology for maximum efficiency; light colour 2700 K; CRI  $\geq$  90; beam angle 32°; degree of protection IP20; Class 3; ceiling base included; Loxone ready;

**General**

Ceiling  
Suspended  
Black Matt + Gold  
IP20  
Interior  
470 lm

**LED**

2700 K  
CRI  $\geq$  90  
L70 / 55000h  
 $\leq$  2 SDCM (initial MacAdam)

**Optical**


Medium  
beam angle 32°

**Electrical**

excl. driver  
24 V  
system 7.0 W  
Class III  
Standard

**Physical**

diameter 100 mm  
height 160 mm  
0.3 kg  
cable length max. 2500 mm  
base included



[28736LBG3] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.