



PROJECT

TYPE


NOTES

QUANTITY

DATE



Ceiling suspended luminaire made from aluminium; surface Black Matt wet painted; matt texture; RAL 9011; inclusive adjustable cable suspension max. 4000mm in Signal Black; with COB (Chip on Board) technology for maximum efficiency; light colour 2700 K; CRI \geq 90; beam angle 32°; degree of protection IP20; Class 3; ceiling base included; Loxone ready;



General

Ceiling _____
 Suspended _____
 Black Matt _____
 RAL 9011 ^a _____
 IP20 _____
 Interior _____
 470 lm _____

LED

2700 K _____
 CRI \geq 90 _____
 L70 / 55000h _____
 \leq 2 SDCM (initial MacAdam) _____

Optical

Medium _____
 beam angle 32° _____

Electrical

excl. driver _____
 24 V _____
 system 7.0 W _____
 Class III _____
 Standard _____

Physical

diameter 100 mm _____
 height 160 mm _____
 0.3 kg _____
 cable length max. 2500 mm _____
 base included _____

^a Colour may deviate slightly due to production conditions

[‘28736LBB3’] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.