WEVER & DUCRÉ LIGHTING

ODREY 1.1 Loxone

28716LBB5

PROJECT

TYPE

NOTES

QUANTITY

DATE

Ceiling suspended luminaire made from aluminium; surface Black Matt wet painted; matt texture; RAL 9011; inclusive adjustable cable suspension max. 4000mm in Signal Black; with COB (Chip on Board) technology for maximum efficiency; light colour 3000 K; CRI ≥ 90; beam angle 32°; degree of protection IP20; Class 3; ceiling base included; Loxone ready;

General

Ceiling
Suspended
Black Matt
RAL 9011 [a]
IP20
Interior
445 lm

LED

3000 K
CRI ≥ 90
L70 / 55000h
≤ 2 SDCM (initial MacAdam)

Optical

Medium
beam angle 32°

Electrical

excl. driver
24 V
system 7.0 W
Class III
Standard

Physical

diameter 55 mm
height 116 mm
0.29 kg
cable length max. 2500 mm
base included

[a] Colour may deviate slightly due to production conditions

['28716LBB5'] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.
© Wever & Ducré BV · Spinnerijstraat 99/21 · 8500 Kortrijk · Belgium · www.weverducre.com